

HELULIGHT® STATIC-RGBW 420

Art. Nr. 11029495

ID 1-000000-07646

EAN Nr. 4260654165425



Normen / Norms

DIN EN 60598-1 :2021/A11:2022 DIN EN 60529 :1991/A2:2013/AC:2019-02

DIN EN 55015:2019+A11:2020 DIN EN IEC 63000:2018

DIN EN 61547:2009

DIN EN 62471:2009




Elektrische Rahmenbedingungen / Electrical characteristic

Netzanschluss / Main Supply	24 VDC
Leistung / Power (W R G B)	8,6W 4,7W 3,9W 3,9W
Dimmbar / Dimmable	PWM
Anschluss / Connection Type	M8, 5-Pol, B-Cod.
Durchschleifbar / Loophthrough	Nein / No
Pinbelegung / Pin assignment	


Licht / Light

Bestückt / Fitted With	LED
Lichtfarbe / Light Colour	5700 K
Lichstrom(Brutto) / Lum. Flux(Gross)(W R G B)	1278lm 187lm 497lm 131lm
Lichstrom(Netto) / Lum. Flux(Net)(W R G B)	1137lm 162lm 406lm 117lm
Effizienz(Brutto) / Efficiency(Gross)(W)	149lm/W
Effizienz(Netto) / Efficiency(Net)(W)	132lm/W
Abstrahlwinkel / Beam Angle	100°
Farbtreue / Colour Rendering	RA / CRI >80
Photobiological Safety	RG-1



Mechanik / Mechanics

Gehäuse / Housing	Aluminium
Abdeckung / Cover	PMMA, Diff.
Drehbar / Rotatable	Nein / No
Gewicht(Netto) / Weight(Net)	0,33 kg
Betriebstemperatur / Operating Temp.	-20°C / +50°C
Lebensdauer / Lifetime	min. 60000 h
Befestigung / Fastening	-



a= 476mm b= 495mm

*Technische Änderungen vorbehalten | technical modifications reserved