

HELULIGHT® WORKPLACE 400



Art. Nr. 11024101

ID 1-000000-07061

EAN Nr. 4260654164732



Normen / Norms

DIN EN 60598-1 :2021/A11:2022

DIN EN 60529 :1991/A2:2013/AC:2019-02

DIN EN 55015:2019+A11:2020

DIN EN IEC 63000:2018

DIN EN 61547:2009

DIN EN 12464-1

DIN EN 62471:2009




Elektrische Rahmenbedingungen / Electrical characteristic

Netzanschluss / Main Supply	230 VAC
Leistung / Power	16,1 W
Dimmbar / Dimmable	stepless
Anschluss / Connection Type	GST18, 3-Pol, -
Durchschleifbar / Loopthrough	Ja / Yes
Pinbelegung / Pin assignment	



Licht / Light

Bestückt / Fitted With	LED
Lichtfarbe / Light Colour	5700 K
Lichstrom(Brutto) / Lum. Flux(Gross)	0 lm
Lichstrom(Netto) / Lum. Flux(Net)	2282 lm
Effizienz(Brutto) / Efficiency(Gross)	0 lm/W
Effizienz(Netto) / Efficiency(Net)	142 lm/W
Abstrahlwinkel / Beam Angle	100°
Farbtreue / Colour Rendering	RA / CRI >80
Photobiological Safety	RG-1



Mechanik / Mechanics

Gehäuse / Housing	Aluminium
Abdeckung / Cover	PMMA, Prism
Drehbar / Rotatable	Nein / No
Gewicht(Netto) / Weight(Net)	1,69 kg
Betriebstemperatur / Operating Temp.	-20°C / +40°C
Lebensdauer / Lifetime	min. 60000 h
Befestigung / Fastening	-



b= 416mm

*Technische Änderungen vorbehalten | technical modifications reserved